

MICRO T-2

## AIMPOINT® MICRO T-2



### AIMPOINT® MICRO T-2

<b>Aiming dot size</b>	2 MOA
<b>Battery type</b>	3V lithium battery, type CR2032.
<b>Battery life - Day time use</b>	5 years (50 000h) of continuous use at pos. 8 and over 10 months at pos. 10. Responds to >500 000 hours at NVD setting (pos. 2)

### OVERVIEW

The Aimpoint® Micro T-2 redefines everything you thought you knew about compact red dot sights. Cutting edge lens coatings radically improve the shape and clarity of the 2 MOA red dot and physical protection has been added for even more ruggedness.

We listened to feedback coming from hard-core customers desiring an even more hard core Micro sight. With a redesigned and reinforced house body, as well as flip-up covers protecting the lenses, the Aimpoint® Micro T-2 can withstand all types of environmental conditions.

At the same time, we decided to improve upon the optical performance of the sight which results in a new lens and an important breakthrough in reflective lens coatings. This makes the Micro T-2 and the 3XMag magnifier a fantastic optical combination.

*Launched 2014.*

### UNIQUE FEATURES

- Advanced optical lenses for even better light transmission
- Front Flip-up lens cover is included
- Transparent rear Flip-up lens cover is included
- Reinforced protection of the turrets for even greater ruggedness
- Ideal for rifles, carbines, shotguns, submachine guns, and handguns
- Weight 3.7 oz. (105g) including mount, sight only 3.0 oz. (84g)
- 1X (non-magnifying) parallax free optic
- Compatible with all generations of Night Vision Devices (NVD)
- 1 Off position, 4 night vision compatible settings and 8 daylight settings – one extra bright for use with laser protection glasses or in bright desert sunlight
- Integral Picatinny-style base allows easy attachment to any rail
- ACET technology allows 50,000 hours (over 5 years) of constant operation with one battery
- Available in 2 MOA dot size
- Hard anodized non-reflective finish
- Submersible to 80 feet (25 meters)
- Use as a standalone sight or piggybacked on larger magnifying, thermal, or night vision optics

# AIMPOINT® MICRO T-2

## TECHNICAL SPECIFICATIONS

GENERAL SPECIFICATIONS
Art.No: 200170
OPTICAL SPECIFICATIONS
<b>Operating principle:</b> Reflex collimator sight with LED
<b>Optical magnification:</b> 1x
<b>Aiming dot size:</b> 2 MOA
<b>Dot intensity:</b> Visible against a background luminance of 0.1 to 55 000 lx
<b>Optical signature:</b> No optical signature is visible at 10 meter distance, front side, on appropriate settings with NVD 3
<b>Dot color:</b> Peak Wavelength: 655 ± 10 nm
<b>NVD compatible:</b> Yes
<b>Optical coating:</b> Anti-reflex, all surfaces and multi-layer. NVD-Compatible 1, 2, 3
<b>Clear aperture:</b> 18 mm
<b>Eye relief:</b> Unlimited

POWER SOURCE
<b>Battery type:</b> 3V lithium battery, type CR2032.
<b>Battery life - Day time use:</b> 5 years (50 000h) of continuous use at pos. 8 and over 10 months at pos. 10. Responds to >500 000 hours at NVD setting (pos. 2)
<b>Power intensity:</b> 4 NVD and 8 Daylight, of which 1 extra bright

PHYSICAL SPECIFICATIONS
<b>Length sight only:</b> 68 mm (2 5/8")
<b>Length conf:</b> 79 mm (3 1/16")
<b>Width:</b> 41 mm (1 9/16")
<b>Height sight only:</b> 36 mm (1 3/8")
<b>Height conf:</b> 47 mm (1 13/16")
<b>Weight sight only (incl battery):</b> 94 g, (3,3 oz)
<b>Weight conf:</b> 130 g (4,6 oz) incl. Lens Covers and Mount
<b>Housing material:</b> High Strength Aluminum
<b>Housing finish and color:</b> Matte black
<b>Material mount and spacer std conf:</b> High Strength Aluminum
<b>Surface treatment:</b> Hard anodized, matte
<b>Height of optical axis - sight and mount:</b> 20 mm (3/4") over top surface of Picatinny/Weaver Rail
<b>Height of optical axis - sight, mount and low spacer:</b> Spacer low: 50 mm (1 15/16") over top surface of Picatinny/Weaver Rail
<b>Height of optical axis - sight, mount and high spacer:</b> Spacer high: 59 mm (2 5/16") over top surface of Picatinny/Weaver Rail
<b>Adjustment:</b> Range ±1 m at 100 meters (±1 yds at 100 yds) in windage and elevation, 1 click = 13 mm at 100 meters = 10 mm at 80 meters = 7/16" at 100 yds

ENVIRONMENTAL SPECIFICATIONS
<b>Temperature range operation:</b> -45°C to 71°C (-49°F to 160°F)
<b>Temperature range storage:</b> -51°C to 71°C (-60°F to 160°F)
<b>Temperature shock:</b> Operable after a temperature shock between -45°C and +71°C. Duration: 4h of Hot +71°C, 4h of Cold -45°C. Cycling: 3 times
<b>Humidity:</b> Operates despite humidity. Limits: RH: 95%, Temp: 20°C to 50 °C, cyclic
<b>Immersion, static:</b> Operates after immersion. Limits: Depth: 25m (83 ft.)
<b>Shock:</b> The unit is operable before and after shock. Limits: X-axis: 500 g, 0.7 - 1.1 ms (3 shocks), Y-axis: 40g ±4g, 11 ±1ms (2 shocks in each direction, Z-axis: 40g ±4g, 11 ±1ms, 2 shocks in each direction. Functional during exposure (room temperature)
<b>Vibration:</b> The unit operates despite vibration. Limits: Vibration, sinusoidal in a frequency range of 10-150 Hz. Frequency: 10-30 Hz, ±1.587 mm, Frequency: 30-150 Hz. 5.75 g, 1 octave/min
<b>Chemical resistance:</b> Withstands occasional contamination of: Hydraulic oil (FSD 8407, Tryckolja 021), Lubricating oil (FSD 8127, Motorolja 5W/30), Lubricating oil (FSD 8220, Smörjfett 220), Lubricating oil (Break Free), Fuels (FSD 8612, Diesel fuel oil), Solvents/cleaning (FSD

MECHANICAL INTERFACE
<b>Keyed surface mount:</b> Integrated