

Polarising microscope KERN OPM-1 · OPN-1 · OPO-1




OPO




OPM



OPN



Bertrand lens, λ Slip, 360° rotatable analyser (removable)



Center-adjustable and turnable polarisation stage



"Swing-Out" condenser

PROFESSIONAL LINE POL

The flexible and powerful polarising microscope for all professional applications with reflected and transmitted light

Features

- These devices are professional, fully-equipped polarising microscopes, which use the polarisation of light to analyse minerals, crystals and isotropic materials
- You can choose between a pure transmitted light variant (KERN OPM), a pure reflected light variant (KERN OPN) and a combi variant (KERN OPO). A complete Koehler illumination is integrated into all series as standard
- As standard, the KERN OPM and OPO transmitted illumination variants have a height-adjustable 0,9/0,13 swing-out Abbe condenser which can be centred, for complete Koehler illumination
- A 360° revolving stage with 1° division, 6' fine division and locking function is integrated into all series as standard
- As standard all series are fitted with a complete polarising unit with scale, a Bertrand lens, a $\lambda + \frac{1}{4} \lambda$ Slip as well as a quartz wedge
- A large selection of accessories such as, for example, a mechanical stage attachment as well as further objectives for a long working distance and filter units are also available
- A protective dust cover, eye cups, as well as multi-lingual user instructions are included in the scope of delivery
- A C-Mount adapter is required to connect a camera. You can select this adapter from the following model outfit list
- Please find detailed information in the following model outfit list

Scope of application

- Mineralogy, texture observations, material testing, observation of crystals

Applications/Samples

- More complex samples with polarising properties

Technical data

- Infinity optical system
- Quintuple nosepiece
- Siedentopf 30° inclined/360° rotatable
- Diopter adjustment: One-sided
- Overall dimensions W×D×H 500×200×500 mm
- Net weight approx. 14,5 kg

STANDARD



Model	Standard configuration				
	Tube	Eyepiece	Objective quality	Objectives	Illumination
OPM 181	Trinocular	WF 10×/ø 20 mm	Infinity Plan	Non-stress 4×/10×/20×/40×	6 V/20 W Halogen (transmitted)
OPN 182	Trinocular	WF 10×/ø 18 mm	Infinity Plan	Non-stress 4×/10×/20×/40×	12 V/50 W Halogen (incident)
OPO 183	Trinocular	WF 10×/ø 18 mm	Infinity Plan	Non-stress 4×/10×/20×/40×/60×	12 V/50 W Halogen (incident) + 6 V/20 W (transmitted)
OPN 184	Trinocular	WF 10×/ø 18 mm	Infinity Plan	Non-stress 4×/10×/20×/40×	12 V/100 W Halogen (incident)
OPO 185	Trinocular	WF 10×/ø 18 mm	Infinity Plan	Non-stress 4×/10×/20×/40×/60×	12 V/100 W Halogen (incident) + 6 V/20 W (transmitted)

Polarising microscope KERN OPM-1 · OPN-1 · OPO-1

Model outfit		Model KERN					Order number
		OPM 181	OPN 182	OPO 183	OPN 184	OPO 185	
Eyepieces (23,2 mm)	WF 10×/18 mm		✓	✓	✓	✓	OBB-A1347
	WF 10×/18 mm (reticule 0,1 mm) (adjustable)		✓	✓	✓	✓	OBB-A1464
	WF 10×/20 mm	✓					OBB-A1351
	WF 10×/20 mm (reticule 0,1 mm) (adjustable)	✓					OBB-A1465
Non-stress Infinity Plan objectives	4×/0,10 W.D. 12,1 mm	✓	✓	✓	✓	✓	OBB-A1294
	10×/0,25 W.D. 4,64 mm	✓	✓	✓	✓	✓	OBB-A1289
	20×/0,40 (spring) W.D. 2,41 mm	✓	✓	✓	✓	✓	OBB-A1290
	40×/0,65 (spring) W.D. 0,65 mm	✓		✓		✓	OBB-A1292
	40×/0,65 (spring) (no cover glass) W.D. 3,9 mm	○	✓	○	✓	○	OBB-A1288
	60×/0,80 (spring) W.D. 0,33 mm	○	○	✓	○	✓	OBB-A1296
Infinity Plan objectives (no cover glass) for long working distance	20×/0,40 W.D. 8,35 mm	○	○	○	○	○	OBB-A1291
	40×/0,65 W.D. 3,90 mm	○	○	○	○	○	OBB-A1293
	50×/0,70 (spring) W.D. 1,95 mm	○	○	○	○	○	OBB-A1295
	80×/0,80 (spring) W.D. 0,85 mm	○	○	○	○	○	OBB-A1297
Trinocular tube	<ul style="list-style-type: none"> · Siedentopf 30° inclined · Interpupillary distance 50 – 75 mm · Light distribution 100:0 · Diopter adjustment: One-sided 	✓	✓	✓	✓	✓	
Professional dedicated polarising trinocular head	To keep the reticular cross in the right-hand eyepiece in the same position, independent of the adjustment of the tube.	○	○	○	○	○	OBB-A1210
Analyser unit with scale	360° rotatable, lockable	✓	✓	✓	✓	✓	
Bertrand lens	Built-in, center-adjustable	✓	✓	✓	✓	✓	OBB-A1121
λ + ¼ λ Slip	λ Slip and ¼ λ Slip (combination)	✓	✓	✓	✓	✓	OBB-A1316
Quartz wedge	I – IV Class	✓	✓	✓	✓	✓	OBB-A1321
Revolving round stage	360° rotatable, center-adjustable, division 1°, Vernier division 6'	✓	✓	✓	✓	✓	
Polarising attached mechanical stage	Polarising attached mechanical stage	○	○	○	○	○	OBB-A1337
Swing-out condenser	N.A. 0,9/0,13 swing-out achromatic condenser (aperture diaphragm)	✓		✓		✓	OBB-A1107
Polarising unit with scale (transmitted)	360° rotatable, lockable	✓		✓		✓	
Koehler illumination	6 V/20 W Halogen spare bulb (transmitted)	✓		✓		✓	OBB-A1370
Reflecting polarising unit replacement bulb	12 V/50 W Halogen		✓	✓	○	○	OBB-A1207
	12 V/100 W Halogen		○	○	✓	✓	OBB-A1377
Colour filters for transmitted illumination	Blue	✓		✓		✓	OBB-A1170
	Green	○		○		○	OBB-A1188
	Yellow	○		○		○	OBB-A1165
	Gray	○		○		○	OBB-A1183
C-Mount	1×	○	○	○	○	○	OBB-A1140
	0,57× (focus adjustable)	○	○	○	○	○	OBB-A1136

✓ = Included with delivery

○ = Option

Pictograms

360° rotatable microscope head	Fluorescence illumination for compound microscopes With 3 W LED illumination and filter	WLAN data interface For transmitting of the picture to a mobile display device
Monocular Microscope For the inspection with one eye	Phase contrast unit For a higher contrast	HDMI digital camera For direct transmitting of the picture to a display device
Binocular Microscope For the inspection with both eyes	Darkfield condenser/unit For a higher contrast due to indirect illumination	PC software To transfer the measurements from the device to a PC.
Trinocular Microscope For the inspection with both eyes and the additional option for the connection of a camera	Polarising unit To polarise the light	Automatic temperature compensation For measurements between 10 °C and 30 °C
Abbe Condenser With high numerical aperture for the concentration and the focusing of light	Infinity system Infinity corrected optical system	Protection against dust and water splashes IPxx The type of protection is shown by the pictogram.
Halogen illumination For pictures bright and rich in contrast	Zoom magnification For stereomicroscopes	Battery operation Ready for battery operation. The battery type is specified for each device.
LED illumination Cold, energy saving and especially long-life illumination	Parallel optical system For stereomicroscopes, enables fatigue-proof working	Battery operation rechargeable Prepared for a rechargeable battery operation
Incident illumination For non-transparent objects	Integrated scale In the eyepiece	Mains adapter 230V/50Hz in standard version for EU. On request GB, AUS or USA version.
Transmitting illumination For transparent objects	SD card For data storage	Power supply Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, AUS or USA on request.
Fluorescence illumination for stereomicroscopes	USB 2.0 digital camera For direct transmitting of the picture to a PC	Package shipment The time required to manufacture the product internally is shown in days in the pictogram.
Fluorescence illumination for compound microscopes With 100 W mercury lamp and filter	USB 3.0 digital camera For direct transmitting of the picture to a PC	

Abbreviations

C-Mount Adapter for the connection of a camera to a trinocular microscope	LWD Long Working Distance	SWF Super Wide Field (Field number at least \varnothing 23 mm for 10 \times eyepiece)
FPS Frames per second	N.A. Numerical Aperture	W.D. Working Distance
H(S)WF High (Super) Wide Field (Eyepiece with high eye point for wearers of glasses)	SLR camera Single-Lens Reflex camera	WF Wide Field (Field number up to \varnothing 22 mm for 10 \times eyepiece)

Your KERN specialist dealer: