



KAHLES

K525i REFINED RELIABLE PRECISION.



5-25x56i

A proven product that offers discerning shooters optimal magnification and reliable performance. Designed to meet the toughest challenges in competition and in the field.

PRODUCT HIGHLIGHTS

- ◆ Ergonomic, shooter-specific configurations for optimal control.
- ◆ True 5x zoom with uncompromised optical performance across the entire adjustment range.
- ◆ Robust competition-grade mechanics built for extreme durability.

FEATURES



First
focal plane



Illuminated
reticle



Main tube
diameter 34 mm



10 MIL per
revolution turrets



Adjustment
direction CCW



Top mounted
parallax



Windage
left or right



EASYREAD



REVOLUTION
INDICATOR




ZERO STOP




TWISTGUARD

RETICLES



SKMR



SKMR4

SCAN TO EXPLORE
OUR PORTFOLIO.



**KAHLES**

K525i REFINED TECHNICAL DATA

Focal plane	FFP
Magnification	5-25
Objective lens diameter (mm)	56
Field of view (ft/100 yds)	23.2-4.9
Exit pupil diameter (mm)	9.5-2.3
Eye relief (mm)	3.74
Diopter compensation (dpt)	+2/-3,5
Twilight factor (DIN 58388)	16.7-37.4
Parallax adjustment (m)	20 - ∞
Impact correction / Click E/W	.1 MRAD
Clicks / Revolution E/W	100/100
Adjustment range E/W (MIL)	29/13
Adjustment range E/W (in/100 yds)	104.4/46.8
Adjustment range E/W (MOA)	100/45
Adjustment direction	CCW
Windage	left/right
Maintube diameter (mm)	34
Length (in)	14.8
Weight (oz)	33.8
Battery type	CR2032
Objective filter thread	M58 x 0.75
Reticles	SKMR4 SKMR
Illumination	✓
EASYREAD	✓
ZEROSTOP	✓
TWISTGUARD	✓
Waterproof (ISO9022-8)	✓
Accessories (optional)	Flip-Up Cover Objective 56 mm / Ocular 46 mm, Sunshield 56 mm, Killflash ARD 56 mm, Parallax Spinner K-1, Throw Lever K-2, Bubble Level 34 mm

SCAN FOR PRICES,
USER MANUAL &
SERVICE SECTION.

