



KAHLES

## K318i REFINED COMPACT VERSATILITY.



3.5-18x50i

All-round compact crossover scope, adaptable to any situation whether short or long range.  
Designed to save rail space and maximise versatility.

### PRODUCT HIGHLIGHTS

- ◆ Ergonomic, shooter-specific configurations for optimal control.
- ◆ True 5x zoom with uncompromised optical performance across the entire adjustment range.
- ◆ Compact design delivering full-size performance.

### FEATURES



First  
focal plane



Illuminated  
reticle



Main tube  
diameter 34 mm



10 MIL per  
revolution turrets



Adjustment  
direction CCW



Top mounted  
parallax



Windage  
left or right



EASYREAD



REVOLUTION  
INDICATOR




ZERO STOP




TWISTGUARD

### RETICLES



SKMR4



MSR2/Ki\*

\* Special order

SCAN TO EXPLORE  
OUR PORTFOLIO.



**KAHLES**

## **K318i** REFINED TECHNICAL DATA

|                                   |                                                                                                                                                     |
|-----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| Focal plane                       | FFP                                                                                                                                                 |
| Magnification                     | 3,5-18                                                                                                                                              |
| Objective lens diameter (mm)      | 50                                                                                                                                                  |
| Field of view (ft/100 yds)        | 28.5-6                                                                                                                                              |
| Exit pupil diameter (mm)          | 6.9-2.8                                                                                                                                             |
| Eye relief (mm)                   | 3.62                                                                                                                                                |
| Diopter compensation (dpt)        | +2/-3,5                                                                                                                                             |
| Twilight factor (DIN 58388)       | 13.2-30.0                                                                                                                                           |
| Parallax adjustment (m)           | 25 - $\infty$                                                                                                                                       |
| Impact correction / Click E/W     | .1 MRAD                                                                                                                                             |
| Clicks / Revolution E/W           | 100/100                                                                                                                                             |
| Adjustment range E/W (MIL)        | 30/15                                                                                                                                               |
| Adjustment range E/W (in/100 yds) | 107.8/53.4                                                                                                                                          |
| Adjustment range E/W (MOA)        | 103/51.6                                                                                                                                            |
| Adjustment direction              | CCW                                                                                                                                                 |
| Windage                           | left/right                                                                                                                                          |
| Maintube diameter (mm)            | 34                                                                                                                                                  |
| Length (in)                       | 12.3                                                                                                                                                |
| Weight (oz)                       | 33.5                                                                                                                                                |
| Battery type                      | CR2032                                                                                                                                              |
| Objective filter thread           | M52 x 0.75                                                                                                                                          |
| Reticles                          | SKMR4<br>MSR2/Ki*                                                                                                                                   |
| Illumination                      | ✓                                                                                                                                                   |
| EASYREAD                          | ✓                                                                                                                                                   |
| ZEROSTOP                          | ✓                                                                                                                                                   |
| TWISTGUARD                        | ✓                                                                                                                                                   |
| Waterproof (ISO9022-8)            | ✓                                                                                                                                                   |
| Accessories (optional)            | Flip-Up Cover Objective 50 mm / Ocular 46 mm,<br>Sunshield 50 mm, Killflash ARD 50 mm, Parallax<br>Spinner K-1, Throw Lever K-2, Bubble Level 34 mm |

\* Special order

SCAN FOR PRICES,  
USER MANUAL &  
SERVICE SECTION.

